

**LKG Home Theatre** connectors and adaptors are the superlative connectors for audio and video perfectionists. There are no better connectors. Both design and machining are attended to with great care. Only the purest metals and plastics are used for body materials. Gold is used extensively for both highly reliable electrical contact areas as well as to provide an unequalled, even luxurious, appearance.

## HOME THEATRE PLUGS & JACKS

- |   |         |                   |  |
|---|---------|-------------------|--|
|    | fig. 1  | <b>45-102G</b>    | RCA PLUG with spring strain relief. Color band identification. One each red and black per package. Maximum cable O.D. 7.0mm                            |
|   | fig. 2  | <b>45-182G</b>    | Right Angle, Solderless RCA Plug, teflon insulation, red and white color band. Maximum cable O.D. 6.0mm.   |
|   | fig. 3  | <b>45-103G</b>    | RCA Plug for RG59/U coaxial cable; twist-on mounting.  |
|   | fig. 4  | <b>45-164G</b>    | Deluxe RCA Plug, red, white and yellow color band for A/V. Maximum cable O.D. 6.0mm. Package of Three.   |
|   | fig. 4  | <b>45-144G</b>    | Deluxe RCA Plug, yellow color band for video. Maximum cable O.D. 6.0mm. Package of Two.  |
|   | fig. 4  | <b>45-104G</b>    | RCA Plug for cables up to 6.0mm (0.24 inches) in diameter. Color band identification on zinc handles; gold contact areas. Pkg. of 1 red and 1 white.   |
|    | fig. 4  | <b>45-204G RD</b> | RCA plug for mini coax cable up to 3.5mm (.137") in diameter. Red color band on Zinc handle, Gold contact area. Package of 2.                          |
|   | fig. 4  | <b>45-204G GR</b> | RCA plug for mini coax cable up to 3.5mm (.137") in diameter. Green color band on Zinc handle, Gold contact area. Package of 2.                        |
|   | fig. 4  | <b>45-204G BU</b> | RCA plug for mini coax cable up to 3.5mm (.137") in diameter. Blue color band on Zinc handle, Gold contact area. Package of 2.                         |
|   | fig. 4  | <b>45-207G</b>    | RCA plug for mini coax cable up to 3.5mm (.137") in diameter. color band on Zinc handle, Gold contact area. Package of 1 red, 1 green & 1 blue.        |
|   | fig. 5  | <b>45-114G</b>    | BNC male for coaxial cables up to 6.0mm O.D. Gold Plated contacts solder terminals. Package of 2.  |
|    | fig. 5  | <b>45-224G RD</b> | BNC Male for mini coax cable up to 3.5mm (.137") in diameter. Red color band on Zinc handle, Gold contact area. Package of 2.                          |
|   | fig. 5  | <b>45-224G GR</b> | BNC Male for mini coax cable up to 3.5mm (.137") in diameter. Green color band on Zinc handle, Gold contact area. Package of 2.                        |
|   | fig. 5  | <b>45-224G BU</b> | BNC Male for mini coax cable up to 3.5mm (.137") in diameter. Blue color band on Zinc handle, Gold contact area. Package of 2.                         |
|   | fig. 5  | <b>45-227G</b>    | BNC male for mini coax cable up to 3.5mm (.137") in diameter. color band on Zinc handle, Gold contact area. Package of 1 red, 1 green & 1 blue.        |
|   | fig. 6  | <b>45-124G</b>    | "F" male for coaxial cables up to 6.0mm O.D. Gold Plated contacts solder terminal. Package of 2.   |
|  | fig. 7  | <b>45-106G</b>    | 4 Pin Mini-Din Male; for cables up to 6mm O.D.. Package of two.  |
|   | fig. 7  | <b>45-186G</b>    | 4 Pin Mini-Din Male; for cables up to 8.0mm O.D.. Package of two.  |
|   | fig. 8  | <b>45-478</b>     | Solderless S-VHS (bulkhead), .625" mounting hole, 4 Pin Mini DIN female-female. Gold plated  |
|   | fig. 8  | <b>42-468</b>     | Solderless S-VHS (bulkhead), .625" mounting hole, 4 Pin Mini DIN female-female Nickel Plated   |
|   | fig. 9  | <b>45-107G</b>    | RCA Jack w/spring strain relief. Color band I.D. Package 1 ea. red and black.  |
|   | fig. 10 | <b>45-105G</b>    | Deluxe RCA Jack, red and white color band for audio. (Left & Right) Maximum cable O.D. 6.0mm. Package of Two.  |
|   | fig. 10 | <b>45-165G</b>    | Deluxe RCA Jack, red, white and yellow color band for A/V. Maximum cable O.D. 6.0mm. Package of Three.   |
|   | fig. 10 | <b>45-145G</b>    | Deluxe RCA Jack, yellow color band for video. Maximum cable O.D. 6.0mm. Package of Two.  |
|  | fig. 11 | <b>45-108G</b>    | RCA Jack, isolated chassis mount. Gold w/color bands. Pack 1 each red and black.   |
|   | fig. 11 | <b>45-128G</b>    | RCA Jack, isolated chassis mount, red and white color band for audio. (Left & Right) Package of Two.   |
|   | fig. 11 | <b>45-138G</b>    | RCA Jack, isolated chassis mount, red, white and yellow color band for A/V. Package of Three.  |
|   | fig. 11 | <b>45-148G</b>    | RCA Jack, isolated chassis mount, yellow color band for video. Package of Two.   |
|   | fig. 12 | <b>45-110G</b>    | RCA Jacks bulkhead feed-thru. An adaptor with RCA females on each end for feeding through panels. For panels up to 5/32" thickness. Color band is red. |
|  | fig. 12 | <b>45-111G</b>    | RCA Jacks bulkhead feed-thru. Same part as above but Color band is BLACK.  |
|   | fig. 13 | <b>45-2700 RD</b> | Recessed chassis mount RCA jack, Gold plated contacts-isolated from panel. Mount in .765" hole, red insulation   |
|   | fig. 13 | <b>45-2700 WH</b> | Recessed chassis mount RCA jack, Gold plated contacts-isolated from panel. Mount in .765" hole, white insulation                                       |
|  | fig. 13 | <b>45-2700 YL</b> | Recessed chassis mount RCA jack, Gold plated contacts-isolated from panel. Mount in .765" hole, yellow insulation                                      |

