

# MICROPHONES CONNECTORS & ADAPTORS

## MICROPHONE CONNECTORS

These cannon type three contact microphone connectors are of die-cast zinc alloy with Nickel plate finish. In-line connectors have rubber strain relief. Locking detent action is incorporated in the design of the Female connectors.



- No. T600J** - 3 Pin (XLR) in-line female
- No. 44-602** - 4 Pin (XLR) in-line female
- No. 44-608** - 5 Pin (XLR) in-line female
- No. 45-690G** - Gold plated, 3 Pin (XLR) in-line female

- No. T600P** - 3 Pin (XLR) in-line male
- No. 44-600** - 4 Pin (XLR) in-line male
- No. 44-604** - 5 Pin (XLR) in-line male
- No. 45-692G** - Gold plated, 3 Pin (XLR) in-line male



- No. F600J** - 3 Pin (XLR) Panel mount female
- No. 44-622** - 4 Pin (XLR) Panel mount female
- No. 44-626** - 5 Pin (XLR) Panel mount female
- No. 45-694G** - Gold plated, 3 Pin (XLR) Panel mount female



- No. F600P** - 3 Pin (XLR) Panel mount male
- No. 44-620** - 4 Pin (XLR) Panel mount male
- No. 44-624** - 5 Pin (XLR) Panel mount male
- No. 45-696G** - Gold plated, 3 Pin (XLR) Panel mount male

For bulk packing, add suffix "B" to the part number

## BALANCED MICROPHONE MATCHING TRANSFORMER

### Low - z to Low - z

This matching transformer adapts all balanced line, low-impedance microphones (150 ohms to 600 ohms) to a standard low impedance phone jack. **No. HL7** It is terminated with a CANNON or Switchcraft type 3-pin female connector and a 1/4" phone plug for inputs requiring low impedance, unbalanced sources. The center tapped primary is grounded to maintain all the advantages of a balanced line low noise pickup and excellent frequency response. Pin one is grounded: Pins 2 & 3 connect to the microphone circuit.



### 3 Pin XLR Female To RCA Adaptors



- No. 44-102** - XLR Female to RCA Male
- No. 44-106** - XLR Female to RCA Female
- No. 44-104** - XLR Male to RCA Male
- No. 44-108** - XLR Male to RCA Female

### 3 Pin XLR To BNC Adaptors



- No. 44-111** - XLR Female to BNC Female
- No. 44-112** - XLR Male to BNC Female

### 3 Pin XLR To 1/4" Phono Adaptors



- No. T630** - XLR Female to 1/4" (mono) Male
- No. T650** - XLR Female to 1/4" (mono) Female
- No. T640** - XLR Male to 1/4" (mono) Male
- No. T660** - XLR Male to 1/4" (mono) Female
- No. 44-114** - XLR Female to 1/4" (stereo) Male
- No. 44-118** - XLR Female to 1/4" (stereo) Female
- No. 44-116** - XLR Male to 1/4" (stereo) Male
- No. 44-120** - XLR Male to 1/4" (stereo) Female

### 3 PIN XLR ADAPTOR:

Use to extend length of microphone cables with 3 Pin male or female XLR connector or can be used as a gender changer.



**No. 70-610**  
Male-Male



**No. 70-620**  
Female-Female

### 3 Pin XLR Female To 3 Pin XLR Male Adaptor (CROSS WIRE PIN 2 & 3)



**No. 44-122**

### 3 PIN XLR ADAPTOR Mini XLR plug to standard XLR jack.



**No. 30-662**

### 3 PIN XLR ADAPTOR Mini XLR plug to standard Plug.



**No. 30-664**

### FEMALE CONNECTOR

For cable connections with spring protector to prevent sharp bending of cable. Includes coupling ring. Brass, nickel plated. Single contact. Coupling ring is removable. Standard 5/8" - 27 thread.



- No. 2317J**
- No. 2317JB** BULK PACKAGED