

HIGH POWER INTEGRATED CIRCUIT MEGAPHONE

20 WATTS CONTINUOUS -25 WATTS MAX.

- ALL WEATHER CONSTRUCTION
- ELECTRONIC SIREN
- EFFECTIVE RANGE OVER 300 YARDS
- VOLUME CONTROL

Big output power with small power consumption. As light as our No. ES15 but with 25 watts maximum power output.

Bell Diameter: 9-1/4"
Length: 14"
Weight: 3 lbs. 5 oz.
Requires: 8 "C" size batteries
(not included)

No. ES25



HIGH POWERED No. ES15 MEGAPHONE

- ALL WEATHER CONSTRUCTION
- ELECTRONIC WAILING SIREN
- EFFECTIVE RANGE: 300 METERS
- HOWL-CANCELLING MIKE

Light enough for single hand control-yet packs enough power to be heard over rough seas or the stormiest weather.

16 WATTS MAXIMUM POWER OUTPUT

Press a button for loud, piercing, continuous siren blare in emergency situations.

Press a switch for speech. A howl-cancelling volume controlled microphone makes speech loud and clear enough to be heard over 300 meters! Complete with shoulder strap.



Bell Diameter: 7.35"
Length: 14.5"
Weight: 3 lbs. 5 oz.
(without batteries)
Requires: 6 "C" size batteries
(not included)

"L" Pad Level Controls

2-1/8" dial plate finished in matte silver and black is supplied. Mounts in 3/8" panel hole 1" long threaded bushing complete with mounting nuts. Includes black plastic contour knob 15 watts RMS at 8 ohms.

STEREO

No. SLP8 8 ohms

MONAURAL

No. LP8 8 ohms



Mono L Pads

No. LP100 100 Watts RMS at 8 Ohms

No. LP50 50 Watts RMS at 8 Ohms

Stereo L Pads

No. LP200 Dual Ganged Attenuators, each
100 Watts RMS at 8 Ohms

No. LP75 Dual Ganged Attenuators, each
50 Watts RMS at 8 Ohms



Control speaker volume in remote high power Hi-Fi or commercial sound installations. Maintain constant loading on amplifier at all volume settings. 3/8" bushing mounts in 3/8" diameter hole.

In addition to reliable operation at full rated load, these attenuators are beautifully styled to be an attractive addition to any sound system. The brushed aluminum face plate is calibrated from 0 dB to infinite attenuation in eleven steps.

ECONOMY 100W STEREO



This lower cost L-Pad has electrical and mechanical specifications similar to those of the No. LP200. Smooth low-noise action provides long lasting sound adjustment capability.

The No. SLP10 is not precisely calibrated to match the decibel markings on No. LP200. A black face plate and knob are supplied as illustrated.

No. SLP10

STEREO 100 WATTS RMS AT 8 OHMS