

High Resolution Wireless RF Mouse



State of the art mouse is great for those who have limited desk top room or hate the wire that limits your mobility. It is compatible with Windows 95/98/2000/ NT / Me. and comes complete with software. The receiver connects at the PS2 port for easy installation.

No. **70-3218** RF Wireless Mouse 800dpi

Features

- >Reliable RF radio technology design
- >Two separate operating channels in 27MHz band. FCC compliant
- >High-Resolution **800dpi**.
- >Operating distance 5ft. (1.5M) minimum.
- >Ergonomically designed to fit hand.
- >Two Buttons + Scroll wheel
- >Requires (2) AAA batteries (included)

High Resolution Wireless IR (infrared ray) Mouse



State of the art mouse is great for those who have limited desk top room or hate the wire that limits mobility. It is compatible with Windows 95/98/2000/ NT / Me. and comes complete with software. The receiver connects at the PS2 port for easy installation.

No. **70-3216** IR Wireless Mouse 520dpi

Features

- >Reliable IR infrared technology design
- >High-Resolution **520dpi**.
- >Operating distance 8ft. (2.5M) minimum.
- >Ergonomically designed to fit hand.
- >Two Buttons + Scroll wheel
- >Requires (2) AAA batteries (included)

IEEE1284 PRINTER CABLES

These cables are fully HP1284 compliant and meet industry standards. They are compatible with most printers, scanners, and Bitronic switch boxes, and are recommended for ALL Ink Jet and Laser Jet Printers.



18 Twisted Pairs w/ >35 Twists/ft.
Double Shielded w/ Heavy Duty Mylar Foil & Braid
28 AWG w/ Stranded Conductors


Standard Printer Cable

- No. **70-1206** DB25 (M) / CEN36 (M) 6'
- No. **70-1210** DB25 (M) / CEN36 (M) 10'
- No. **70-1225** DB25 (M) / CEN36 (M) 25'
- No. **70-1250** DB25 (M) / CEN36 (M) 50'

PORT RECONFIGURATION KIT

This kit provides a simple way to either reconfigure to compensate for non-standard wiring or to customize and add additional components such as surge protection. There is no continuity from one end to the other without wiring the jumpers to the device.

No. **C125** DB25 (M) / (F)



WIRING ADAPTOR BREAKOUT BOX

This device allows you to wire the DB25 connector to your PC through the use of the internal printed circuit board and included jumper wires. The unit is reusable and requires NO soldering.

No. **C130** DB25 (M) / (F)



RS232 TESTER DEVICE

This handy item allows quick checking of data signals. Seven LED's monitor the status of the standard RS232 lines to determine if the trouble is emanating from the equipment or the cable.

No. **C120**

