

HDMI™ EXTENSION CABLES**HDMI 19 Pin / Male - HDMI 19 Pin / Female**

Philmore HDMI extension cables use industry standard 28 AWG cable. Both HDMI 19 Pin (version 1.2) Male & Female connectors are Gold plated and come with dust covers to protect connectors from damage during transit and show room environment. HDMI does not specify a maximum cable length but it specifies the required performance of a cable by their licensed manufacturers. We do not recommend to use or extend HDMI 28 AWG cable in total length to exceed 6-7 meters (19.7 - 23.0 feet). These extension cables can be used with our No. 45-7131 thru No. 45-7135 (1 meter thru 5 meters).

Philmore Part No.	Description	Cable DIA.	Length (feet)
No. 45-7231	HDMI 1.2 19 PIN, 28 AWG Cable	7.3 mm	1 meters (3.28')
No. 45-7232	HDMI 1.2 19 PIN, 28 AWG Cable	7.3 mm	2 meters (6.56')

**HDMI™ FLAT CABLES**

A perfect solution for a traveller or an installer with limited space with which to work. Philmore HDMI flat cable is easy - to - carry and store. Cable is approximately 1/8" (.125") thick, 1 meter (3.28') cable weighs less than 4 oz. and can be folded to fit inside your shirt pocket. These flat cables are manufactured to meet HDMI specifications.

Philmore Part No.	Description	Cable Width	Length (feet)
No. 45-7101	HDMI 1.2 19 PIN, Flat Cable	13 mm (.51")	1 meters (3.28')
No. 45-7102	HDMI 1.2 19 PIN, Flat Cable	13 mm (.51")	2 meters (6.56')

**HDMI™ CABLE WITH REPEATER**

Philmore HDMI cable with repeater will allow you to customize your installation where extra cable lengths are needed. It works by regenerating the high definition video and digital audio it receives from the source and transmitting it to HDMI display. Cable is CL3/CMG rated for In-Wall installation.

Specifications:

HDMI Male - Male

- * Self powered active circuitry
- * Supports HDMI audio & video
- * Resolutions: 1080P, 1080I, 720P, 480P, & 480I
- * Supports computer resolutions: UXGA, SXGA, XGA, SVGA, & VGA
- * Total transmitting range:
 - 1080P - 25M total length
 - 1080I / 720P - 30M total length

- * Status indicator lights



No. 45-7140 - 15 meters (49 ft.)



No. 45-7141 - 20 meters (65.5 ft.)

No. 45-7143 - 30 meters (98 ft.)

NOTE: will also work with DVI (requires DVI adaptor **No. 45-7047**)