

# SWITCHES STANDARD TOGGLE


## STANDARD SIZE BAT HANDLE TOGGLE SWITCHES

### SPECIFICATIONS:

<b>Current Rating:</b>	3A @ 125V AC, 1A @ 250V AC
<b>Initial Contact Resistance:</b>	5 Meg ohm (Max.)
<b>Insulation Resistance:</b>	100 Meg ohm (Min.) @ 500V DC
<b>Dielectric Strength:</b>	1000V AC 50/60 Hz for 1 minute
<b>Contact Material:</b>	Brass - Nickel Plate
<b>Terminal Material:</b>	Brass - Nickel Plate
<b>Terminal Type:</b>	Solder

Part No.	Replaces	Type	Action			Actuator
30-219	219	SPST	ON	-	OFF	Metal
30-221	221	DPDT	ON	-	OFF	Metal

Part No.	Type	A	B	Depth	C	D	E
30-219	SPST	1"	1-21/32"	9/16"	9/16"	13/32"	1/2"
30-221	DPDT	1-5/32"	1-13/16"	22/32"	11/16"	13/32"	1/2"



Mounting Hole: 0.500"  
Bushing .472 OD




## STANDARD SIZE BAT HANDLE TOGGLE SWITCH

### SPECIFICATIONS:

<b>Current Rating:</b>	6A @ 125V AC, 3A @ 250V AC
<b>Initial Contact Resistance:</b>	5 Meg ohm (Max.)
<b>Insulation Resistance:</b>	100 Meg ohm (Min.) @ 500V DC
<b>Dielectric Strength:</b>	1000V AC 50/60 Hz for 1 minute
<b>Contact Material:</b>	Brass - Nickel Plate
<b>Terminal Material:</b>	Brass - Nickel Plate
<b>Terminal Type:</b>	Screw

Part No.	Replaces	Type	Action			Actuator
30-226	226A	DPDT	ON	OFF	ON	Metal



Mounting Hole: 0.500"




## STANDARD SIZE BAT HANDLE TOGGLE SWITCH

### SPECIFICATIONS:

<b>Current Rating:</b>	10A @ 125V AC, 6A @ 250V AC
<b>Initial Contact Resistance:</b>	50 Meg ohm (Max.)
<b>Insulation Resistance:</b>	DC 500V 100 Meg ohm (Min.)
<b>Dielectric Strength:</b>	AC 1500V 1 minute
<b>Bushing Material:</b>	Brass - Nickel Plate, M12-.75 Threads
<b>Terminal Material:</b>	Brass - Nickel Plate
<b>Terminal Type:</b>	Screw

Part No.	Type	Action			Actuator
30-10124	SPDT	ON	-	ON	Brass Nickel Plate
30-10126*	SPDT	ON	-	ON	Brass Nickel Plate

(\* = 30-10126 has .250" Quick connect terminal.)



Mounting Hole: 0.500"




## STANDARD SIZE BAT HANDLE TOGGLE SWITCH

### SPECIFICATIONS:

<b>Current Rating:</b>	15A @ 125V AC, 10A @ 250V AC
<b>Initial Contact Resistance:</b>	50 Meg ohm (Max.)
<b>Insulation Resistance:</b>	DC 500V 100 Meg ohm (Min.)
<b>Dielectric Strength:</b>	AC 1500V 1 minute
<b>Bushing Material:</b>	Brass - Nickel Plate, M12-.75 Threads
<b>Terminal Material:</b>	Brass - Nickel Plate
<b>Actuator Type:</b>	Metal (Brass Nickel Plate)

Part No.	Type	Action			Terminal
30-10099	SPDT	(ON)	OFF	(ON)	Solder
30-10351	SPDT	(ON)	OFF	(ON)	Screw

NOTE: ( ) = Momentary



Mounting Hole: 0.500"

