


SPECIFICATIONS:

Current Rating:	15A @ 125V AC, 7.5A @ 250V AC
Initial Contact Resistance:	5 Meg ohm (Max.)
Insulation Resistance:	100 Meg ohm (Min.)
Dielectric Strength:	1000V AC for 1 minute
Contact Material:	Copper Alloy
Terminal Material:	Copper Alloy
Terminal Type:	.250" Quick Connect


Part No.	Type	Action			Actuator
30-390	SPST	ON	-	OFF	Amber Nylon
30-395	SPST	ON	-	OFF	Red Nylon
30-16740*	SPST	ON	-	OFF	Translucent Nylon

*30-16740 RATED 16A @ 125VAC, 10A @ 250VAC
Neon Light @ 110V AC

LIGHTED ROCKER SWITCHES



Mounting Hole: 1.125" x 0.550"




SPECIFICATIONS:

Current Rating:	16A @ 125V AC, 12A @ 250V AC 3/4 HP @ 125-250V AC, 10A @ 14V DC
Initial Contact Resistance:	5 Meg ohm (Max.)
Insulation Resistance:	100 Meg ohm (Min.)
Dielectric Strength:	1000V AC for 1 minute
Contact Material:	Copper Alloy
Terminal Material:	Copper Alloy
Terminal Type:	.250" Quick Connect

Part No.	Type	Action			Actuator
30-710	SPST	ON	-	OFF	Black Nylon
30-720	SPDT	ON	-	ON	Black Nylon
30-730	SPST	ON	-	OFF	Green Nylon*
30-740	SPST	ON	-	OFF	Amber Nylon*

*Lamp (is dependent) high intensity neon with 1/4 watt 22 K Ohm resistor, with 10,000 hours of life for 125 volts.

APPLIANCE ROCKER SWITCHES



Mounting Hole: 1.125" x 0.550"



SPECIFICATIONS:

ELECTRICAL RATINGS:		
15A	125-250V AC T85	UL E45221
1/2HP	125V AC 1HP 250V	UL E45221
16A	125-250V AC Res	CSA LR10990
16 (4)A	250V AC T85	VDE 45152
20A	28V DC	Approvals N/A

MATERIALS:


Body:	Nylon 6.6
Actuator Transparent:	Polycarbonate
Contact Gap:	u Micro
Contact Material:	Silver Alloy

Part No.	Type	Action			Actuator
30-060	SPST	ON	-	OFF	Red Lens*
30-069	SPST	ON	-	OFF	Red Translucent**

* Lamp Voltage 12V AC/DC Incandescent

** Lamp Voltage 105-130V AC Neon

LIGHTED STANDARD SIZE ROCKER SWITCHES



* NOTE: User Note: The light bulb incorporated in this switch must be connected to 12 volts AC or DC and NOT to 125 volts. The 125 volt rating applies to switch contacts, NOT to the light.

SPECIFICATIONS:

ELECTRICAL RATINGS:		
15A	125-250V AC T85	UL E45221
1/2HP	125V AC 1HP 250V	UL E45221
16A	125-250V AC Res	CSA LR10990
16 (4)A	250V AC T85	VDE 45152
20A	28V DC	Approvals N/A


MATERIALS:

Body:	Nylon 6.6
Actuator Transparent:	Polycarbonate
Contact Gap:	u Micro
Contact Material:	Silver Alloy

Part No.	Type	Action			Actuator
30-550	SPST	ON	-	OFF	Red Lens*
30-552	SPST	ON	-	OFF	Green Lens*
30-556	SPST	ON	-	OFF	Amber*

* NOTE: User Note: The light bulb incorporated in this switch must be connected to 12 volts AC or DC and NOT to 125 volts. The 125 volt rating applies to switch contacts, NOT to the light.

LIGHTED STANDARD SIZE SNAP-IN ROCKER SWITCHES



Lead Terminal 1, Line In terminal
2, Line Out terminal 3.
Light will be ON or OFF when
switch is In ON or OFF position.
12V AC/DC Incandescent

