

MAGNETIC REED SWITCH

SPECIFICATIONS:

Current Rating:	.5A @ 100VDC		
Initial Contact Resistance:	300 Meg ohm (Max.)		
Operating Gap:	1.25" Max		
Mounting Centers:	2.094" (2-3/32")		
Mounting Hole:	.15" (Max.)		
Terminal Type:	Screw		
Part No.	Type	Action	Actuator
30-17050	SPST	N.C (Normally closed) when magnet is within actuation range	Magnet



N.O./N.C. MAGNETIC REED SWITCH

SPECIFICATIONS:

Current Rating:	0.5A @ 20V DC, 10 Watts (Max.)			
Voltage Rating:	120V AC (Max.) @ 0.08A 80V DC (Max.) @ 0.1A			
Contact Material:	Iron Alloy - Gold Plate			
Terminal Material:	Plated Steel			
Terminal Type:	Screw			
Part No.	Replaces	Type	Action	Actuator
30-10072	10072	SPDT	Normally open w/o magnet Normally closed w/o magnet	Magnet



Mounting Center: 2.125"

MAGNETIC REED SWITCH

SPECIFICATIONS:

Current Rating:	.5A @ 100VDC/125VAC		
Initial Contact Resistance:	300 Meg ohm (Max.)		
Operating Gap:	.90" Max		
Mounting Centers:	1.56" (1-9/16")		
Mounting Hole:	.134" (Max.)		
Terminal Type:	Screw		
Part No.	Type	Action	Actuator
30-17051	SPST	N.O. (Normally Open) when magnet is within actuation range	Magnet



LOW PROFILE MAGNETIC REED SWITCH

SPECIFICATIONS:

Current Rating:	.5A @ 100VDC/125VAC		
Initial Contact Resistance:	300 Meg ohm (Max.)		
Operating Gap:	.60"-1.5"		
Mounting Centers:	1"		
Mounting Hole:	.125" (Max.)		
Terminal Type:	10" Leads, 24 AWG		
Part No.	Type	Action	Actuator
30-17054	SPST	N.O. (Normally Open) when magnet is within actuation range	Magnet

